

# WSTB-710

Digital HD Cable Receiver

## Main Feature

- Fully DVB-C(EN300429) compliant
- H.264/MPEG-4 AVC HP@L4.1, MPEG-2 MP@HL
- Conax CAS Embedded
- AV output: CVBS and Stereo Audio
- HDMI output
- One touch & Schedule Recording Function
- Multiple Display Mode: 1080p/1080i/720p/576p/576i
- Aspect ratio 4:3/16:9, Letter box, Full Screen, Auto, Pan&Scan
- Electronic Program Guide for 7 Days
- Teletext Supported through VBI and OSD
- Multi-language subtitle supported
- Multi-Audio supported
- Program management
- Favorite program setting
- Parental Control supported
- LCN supported



## Specification

Tuner & Channel Decoder	RF Connector Input	F type
	RF Connector Output	IEC type
	Frequency Range	51-860MHz
	Input impedance	75Ω
	IF bandwidth	8 MHz
	Demodulation	16/32/64/128/256QAM
	Symbol rate	1~7Mbps
Video Decoding	Transport stream	ISO/IEC 13818-2
	Profile Level	H.264/AVC,MPEG-2 MP@HL,MPEG-4 SP@ASP, VC-1, RealMedia
	Aspect Ratio	4:3, 16:9
	Video Resolution	576i, 576P, 720P, 1080i,1080P
Audio Decoding	Video Sync Scope	300mVp-p
	Standard	ISO/IEC 13818-3
	Audio Decoding	MPEG-1 layer I/II, MPEG-2 layer II,MP3 MPEG-4 AAC/AAC+, AC-3,E-AC-3,WMA
	Audio Mode	Single/Dual mono/Stereo
	Sample Frequency	16/22.05/24/32/44.1/48 kHz
	Audio Output Level	0-6 dBu
	Volume Level	32 Levels
Rear panel	HDMI/ HDCP	1.3
	3.5mm Connector	CVBS & Stereo Audio
	S/PDIF	Coaxial Digital Audio Output
	USB	USB 2.0
	LAN	RJ-45
Power Supply	Adaptor Input Voltage	AC 100~240V 50/60Hz
	Power Supply	DC 5V/2 A
	Power consumption	Standby <1W, Working <8W
Physical	Dimensions	W 230 mm x H 28 mm x 175 mm
	Operating temperature	0-40°C